

Claims

What is claimed is:

1. An apparatus for testing a leakage rate within a recuperator core, said recuperator core having a plurality of components, such components being a plurality of cells being welded one to another, said apparatus comprising:
- a platform defining a first end and a second end, a first surface of the platform extends between said first end and said second end, a first support portion being attached to said first surface and a second support portion being spaced from said first support portion and each being attached to said first surface;
 - a pair of sealing mechanisms, at least one of said pair of sealing mechanisms being movable between an open or non testing position and a closed or testing position, in said closed or testing position a reservoir being formed ;
 - a pump being operatively connected to at least one of said pair of sealing mechanisms;
 - a monitoring system being operatively connected to said platform, said pair of sealing mechanisms, said reservoir and said pump; and
 - a readout station being operatively connected to said monitoring system, said reservoir and said pump.
2. The apparatus for testing a leak within a recuperator core of claim 1, wherein said monitoring system includes a plurality of sensors.
3. The apparatus for testing a leak within a recuperator core of claim 2, wherein said plurality of sensors operational sensing said pair of sealing mechanisms being in said closed or testing position.

10023585-121701

July 1982

10301

4. The apparatus for testing a leak within a recuperator core of claim 1, wherein said monitoring system has a plurality of safety devices operatively attached thereto.
5. The apparatus for testing a leak within a recuperator core of claim 1, wherein said readout station has a visual indicator.
6. The apparatus for testing a recuperator core of claim 5 wherein readout station visually marks a result of said tested recuperator core on said recuperator core.
7. The apparatus for testing a recuperator core of claim 6 wherein said readout station indicates a decay rate of said recuperator core.
8. The apparatus for testing a recuperator core of claim 2 wherein said plurality of sensors define that said pair of sealing mechanisms are at said open or non-testing position.
9. The apparatus for testing a recuperator core of claim 1 wherein said pump is a vacuum pump.
10. The apparatus for testing a recuperator core of claim 9 wherein a rate of decay has a predefined acceptable rate and a predefined rejection rate for said recuperator core.
11. A method of testing a recuperator core, said recuperator core having a plurality of donor passages defining a donor inlet end and a donor outlet end and a plurality of recipient passages defining a recipient inlet end and a recipient outlet end, said plurality of donor passages being sealed from said

100 Years of the 1917 1918 1919 1920 1921 1922 1923 1924 1925 1926 1927 1928 1929 1930 1931 1932 1933 1934 1935 1936 1937 1938 1939 1940 1941 1942 1943 1944 1945 1946 1947 1948 1949 1950 1951 1952 1953 1954 1955 1956 1957 1958 1959 1960 1961 1962 1963 1964 1965 1966 1967 1968 1969 1970 1971 1972 1973 1974 1975 1976 1977 1978 1979 1980 1981 1982 1983 1984 1985 1986 1987 1988 1989 1990 1991 1992 1993 1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100

positioning a sealing member in sealing relationship with one of
 et end and said recipient inlet end and positioning an other of said
 er in sealing relationship with one of said donor outlet end and said
 t end forming a reservoir and defining a closed or testing position;

monitoring a rate of decay of said pressure and said vacuum; and
displaying said rate of decay.

13. The method of testing the recuperator core of claim 11 said step of displaying said rate of decay, said sealing member in relationship with one of said donor inlet end and said recipient inlet end of said sealing member in sealing relationship with one of said donor inlet end and said recipient outlet end are disengaged from said closed or testing position into an open or non testing position and said tested core being one of an operational core position and a failed core position.

14. The method of testing the recuperator core of claim 11 wherein prior to said step of positioning said recuperator core in said test stand

Sub
18
Cont

said recuperator core having a guard member position about an "OD" of said recuperator core.

15. The method of testing the recuperator core of claim 11 including positioning a plurality of sensors being operatively connected to said pair of sealing mechanisms and said controller, and said plurality of sensors sensing the proper position of said pair of sealing mechanisms relative to an open or non testing position and said closed or testing position and communicate a signal to said controller before applying one of the pressure and the vacuum to said reservoir.

16. The method of testing the recuperator core of claim 15 including said plurality of sensors include a plurality of safety devices operatively attached to said controller.

17. The method of testing the recuperator core of claim 11 wherein said step of displaying said decay rate includes a readout station.

18. The method of testing the recuperator core of claim 17 wherein said readout station being a viewable screen.

19. The method of testing the recuperator core of claim 17 wherein said readout station printing a decay rate on said recuperator core.

20. The method of testing the recuperator core of claim 17 wherein said readout station indicating said decay rate defines as a loss of one of a pressure and vacuum per a unit of time.

1002355 12101